

Amorim Cork South Africa (Pty) Ltd. Quality Assurance Department

PRODUCT SPECIFICATION



Agglomerated Champagne Cork – Colours

Available sizes: 47 × 29.5 mm

| TESTS | CHARACTERISTICS | SPECIFICATION |
|---------------------|--|---------------|
| PHYSICAL-MECHANICAL | Length ¹ | ± 1.0 mm |
| | Diameter ¹ | ± 0.3 mm |
| | Ovality ¹ | ≤ 0.3 mm |
| | Average Weight ¹ | X ± 1 gr |
| | Density ¹ | 230-330 Km/m³ |
| | Moisture ² | 4% – 8% |
| | Torsion Moment ¹ | ≥ 25 daN |
| | Torsion Angle ¹ | ≥ 30° |
| | Shear strength ¹ | ≥ 6.0 |
| PHYSICAL-CHEMICAL | Releasable TCA (average batch result) ³ | < 1.5 ng/L |
| PRINTING | Traceability code +/ client specification | |
| VISUAL GRADING | As per client specification agreed between Amorim and customer | |

a) Amorim Corks are adequate to be in contact with food products, in compliance with Regulation (EC) No. 1935/2004, and Resolution ResAP (2004). All products used during production are adequate to be in contact with foodstuffs, in compliance with Directive 2002/72/CE and 94/62/CE and FDA 21CFR part 175. Cork has the potential to be recycled according to these requirements.

- b) Analysis: $^1\!\text{based}$ on A&I's test report; $^2\!\text{Amorim SA}$ analysis; $^3\!\text{Independent Laboratory analysis}.$
- c) Amorim Corks are produced and controlled at Amorim & Irmãos Portugal, according to their Quality Management System (ISO 9001), Food Safety management system (ISO 22000) and to the International Code of Cork Stopper Manufacturing Practices.

PRODUCTION FLOWCHART

